Abante Civil SMEs of 106 12015 Application Surrace preparation with Birla putty to match the old state of the preparation with birla putty. 1 coat of exterior primer including suface Preparation with birla putty. 2 coats of exterior emulsion paint (Elastomeric, Sun Reflect, Dirt Resistance) of the product used of the	Plaster Patches Repair and Surface Preparation Work, Including Spider Man Charges on Balcomy Facia's Description: a.Providing and applying a coat of bonding agent Nito bound or equivalent. b.Providing and applying a coat waterproofing using URP301. c.Providing & Laying of Plaster with ready-mix mortar (Only UltraTech). The plaster should be applied in One layer: 10mm to 12mm thickness. d. Providing and applying a coat of curing Compound. e. Providing and applying a coat of curing Compound. e. Providing and applying a of layer level plast on existing surface to match the old and new surface upto 5mm thick. e. Provide and apply an acid wash where algae growth is observed. Ensure proper treatment before paint application. Surface preparation with Birla putty. 1 coat of exterior emulsion paint (Elastomeric, Sun Reflect, Dirt Resistance) of approved color and shade. This work must be done at all heights and levels, with all necessary surface preparation. (8 yearwarranty Paint product used) Make - Berget. Social Security Paint product used) Make - Berget. Social Security Paint product used) Make - Berget. Social Security Paint product used of the proper security of approved color and shade. This work must be done at all heights and levels, with all necessary surface preparation. (8 yearwarranty Paint product used) Make - Berget. Social Security Paint Product used of the proper security of approved color and shade. Tech.Manager Mr Udairaj Singh Mr Udairaj Singh Infra Compittee in the proper security of the provide and new surface preparation. Provide and apply apply and apply apply and	Sqm 1800 Sqm 3000 Sqm 3000 Sqm ATENDRA S IN 6.H S ATENDRA S IN 6.H S ATENDRA S IN 6.H Authori
application. Surrace preparation with Bir 1 coat of exterior primer including suface 2 coats of exterior emulsion paint (Elastor This work must be done at all heights and (8 year/Warranty Paint product used) /// [Syear/Warranty Paint product used) /// [Ing as per actual site Measurment ecutive Civil	ing agent Nito bound or equivalent. Ifing using URP301. By-mix mortar (Only UltraTech). The plaster should be applied in One layer: Ig Compound. Ig compound. Ig age growth is observed. Ensure proper treatment before paint lift a putty. Ig prepration with birla putty. Ig erepression with all necessary surface preparation. Ig with all necessary surface preparation. Ig with any to be rectified by mutual Discussion. Ig age growth is observed. Ig age growth is observed. Ig compound. Ig age growth is observed. Ig compound. Ig age growth is observed. Ig compound. Ig compoun	
application, surrace preparation with Bir 1 coat of exterior primer including suface 2 coats of exterior emulsion paint (Elastor This work must be done at all heights and (8 yearWarranty Paint product used) /// :- 1. Before Patch Repair Seepage is ling as per actual site Measurment ecutive Civil	ing agent Nito bound or equivalent. fing using URP30.1. dy-mix mortar (Only UltraTech). The plaster should be applied in One layer: Ig Compound. last on existing surface to match the old and new surface upto 5mm thick. last on existing surface to match the old and new surface upto 5mm thick. Te Prepration with birla putty. Is a putty to match the old surface, followed by: It issue if any to be rectified by mutual Discussion. It issue if any to be rectified by mutual Discussion.	
application, surrace preparation with Bir 1 coat of exterior primer including suface 2 coats of exterior emulsion paint (Elastor This work must be done at all heights and (8 yearWarranty Paint product used) /// 1. Before Patch Repair Seepage is ling as per actual site Measurment	ing agent Nito bound or equivalent. fing using URP301. dy-mix mortar (Only UltraTech). The plaster should be applied in One layer: g Compound. last on existing surface to match the old and new surface upto 5mm thick. last on existing surface to match the old and new surface upto 5mm thick. prepration with birla putty. ce Prepration with birla putty. omeric, Sun Reflect, Dirt Resistance) of approved color and shade. of levels, with all necessary surface preparation. fig kc - Beyer. issue if any to be rectified by mutual Discussion.	
application. Surrace preparation with Bir 1 coat of exterior primer including suface 2 coats of exterior emulsion paint (Elastor This work must be done at all heights and (8 year/Warranty Paint product used) /** :- 1. Before Patch Repair Seepage is ing as per actual site Measurment	ing agent Nito bound or equivalent. Ifing using URP301. Ig Compound. Igs Compound. Igse growth is observed. Ensure proper treatment before paint ifina putty to match the old surface, followed by: Prepration with birla putty. Omeric, Sun Reflect, Dirt Resistance) of approved color and shade. Id levels, with all necessary surface preparation. Issue if any to be rectified by mutual Discussion.	
application. Surrace preparation with Bir 1 coat of exterior primer including suface 2 coats of exterior emulsion paint (Elastor This work must be done at all heights and (8 year/Warranty Paint product used) /1. 1. Before Patch Repair Seepage is	ing agent Nito bound or equivalent. fing using URP301. dy-mix mortar (Only UltraTech). The plaster should be applied in One layer: g Compound. last on existing surface to match the old and new surface upto 5mm thick. algae growth is observed. Ensure proper treatment before paint lirla putty to match the old surface, followed by: be Prepration with birla putty. ce Prepration with birla putty. di levels, with all necessary surface preparation. fig kc - Beget. issue if any to be rectified by mutual Discussion.	
application. Surrace preparation with Bir 1 coat of exterior primer including suface 2 coats of exterior emulsion paint (Elastor This work must be done at all heights and (8 year/Warranty Paint product used) ////	ing agent Nito bound or equivalent. fing using URP301. dy-mix mortar (Only UltraTech). The plaster should be applied in One layer: g Compound. last on existing surface to match the old and new surface upto 5mm thick. algae growth is observed. Ensure proper treatment before paint sirla putty to match the old surface, followed by: ce Prepration with birla putty. omeric, Sun Reflect, Dirt Resistance) of approved color and shade. d levels, with all necessary surface preparation. fig. K. — Beyer.	
Provide and apply an acid wash where al	paration Work, Including Spider Man Charges on Balcony Facia's ing agent Nito bound or equivalent. fing using URP301. dy-mix mortar (Only UltraTech). The plaster should be applied in One layer: g Compound. last on existing surface to match the old and new surface upto 5mm thick.	
Plaster Patches Repair and Surrace Preparation Work, including Spider M Description: a.Providing and applying a coat of bonding agent Nito bound or equivalent b.Providing and laying a coat waterproofing using URP301. c.Providing & Laying of Plaster with ready-mix mortar (Only UltraTech). The 10mm to 12mm thickness. d. Providing and applying a coat of curing Compound. e. Providing and laying a of layer level plast on existing surface to match the personner.		
Plaster Patches Repair and Surface Preparation Work, Including Spider M Description: a.Providing and applying a coat of bonding agent Nito bound or equivalent b.Providing and laying a coat waterproofing using URP301. c.Providing & Laying of Plaster with ready-mix mortar (UltraTech). The plas and 10mm thickness. d. Providing and applying a coat of curing Compound. e. Providing and laying a of layer level plast on existing surface to match the f.Plaster falling on existing Good surface to be Cleaned same day.	Plaster Patches Repair and Surface Preparation Work, Including Spider Man Charges on Tower's Description: a.Providing and applying a coat of bonding agent Nito bound or equivalent. b.Providing and laying a coat waterproofing using URP301. c.Providing & Laying of Plaster with ready-mix mortar (UltraTech). The plaster should be applied in two layers: 15mm and 10mm thickness. d. Providing and applying a coat of curing Compound. e. Providing and laying a of layer level plast on existing surface to match the old and new surface upto 5mm thick. f.Plaster falling on existing Good surface to be Cleaned same day.	3
Provide and lay chicken wire mesh at ju	1. Provide and lay chicken wire mesh at junction of RCC & Brick work secured with concrete nails, and fill gaps.	Sqm
Removing, scraping, and dismantling exist square or rectangular in shape Exiesting f properly.	Removing, scraping, and dismantling existing damaged plaster up to the brick level surface. Patches to be Made square or rectangular in shape Exiesting from grove to grove . Including Spider Man Charges.Covering & Cleaning properly.	Sqm
	Particular	Unit
	Façade Patch Repair & Painting Work (Tower & Balconies	onies)
	The World Spa Sec-30/41	
	The World Spa Sec-30/41	
ntling exis	The World Spa Sec-30/41 Façade Patch Repair & Painting Work (Tower & Balconi Particular Particular isting damaged plaster up to the brick level surface. Patches to be Made from grove to grove . Including Spider Man Charges. Covering & Cleaning	