

The World Spa Apartment Owners Association

Sector - 30/41 Gurugram


BOQ for Automatic Boom Barrier Model - IDT Pro 4

S.No	Description	Make	UOM	Quantity	Rate	Amount
1	Supply and installation of Automatic Boom Barrier Model IDT Pro 4 , Running speed 3sec , boom length 4.5m, boom type Telescopic existing boom barrier dimension 335mm x285mm x925mm, input voltage 220V, working temp upto 60c degree, boom dimension 45mm x100mm inclosure rating IP55	ID Tech	Nos	5		

Features:-

1	Wheel manual release. incase of power off, rotate the wheel manual release on the bottom of the motor to raise the boom manually . When power on, the motor will work normally.					
2	Machine core with strong and double springs, make the machine core works more steadily					
3	Die-casting aluminium alloy motor, precise and good at thermal radiation					
4	Crank and rod structure makes the boom run placidly.					
5	Reversing on obstacle					
6	Auto-closing					
7	Support the infrared photocell for anti-bumping function (Optional)					
8	Support Loop detector (optional)					
9	Wire control (switch signal)/remote control					
10	Digital limit, more precise					


Udayraj Singh
Technical Manager


Harpreet Singh
Estate Head

Authorised BOM
TWSAOA