

The World Spa Apartment Owners Association					
Sector - 30/41 Gurugram					
BOQ For Basement Detection System					
	Description	MAKE	QTY	Model No.	UNIT
1	Supply of 2 Loop Addressable Panel which supports 254 devices in any combination, 4.3-inch LCD display screen, Wired and Wireless device support on the same loop, Builtin Thermal Printer for logs printing of events, Ethernet, RS-485, and IoT port for Enabling access to the Wisualarm cloud platform for seamless, one-stop monitoring andmanagement.built-in 12V/5Ah batteries	DAHUA	2	DHI-HY-1025R	Nos.
2	Bus LoRa Gateway DHI-WG-1037 serves as a bridge between LoRa devices and fire alarm control panels. Gateway can connect Up to 32 LoRa devices, operating Voltage DC16V-DC28V, Distance covers Free space: 2maximum of 1500 metres ordinary walls: maximum of 5 walls	DAHUA	4	DHI-WG-1037	Nos.
3	Supply of Dahua Wireless LoRa Smoke Detector DHI-HY-L131 can be connected to the Addressable Fire Alarm Control Panel. Compatible with wireless gateway distance upto Free space: a maximum of 1500 metres Ordinary walls: 3-5 , with inbuilt Sounder	DAHUA	25	DHI-HY-L131	Nos.
4	Supply of wireless LoRa Manual Call Point DHI-HY-L121 can be connected to the Addressable Fire Alarm Control Panel. Compatible with wireless gateway, Alarm: Red indicator flashes once every second Fault: Yellow indicator flashes once every minute Standby: Green indicator flashes once everyminute	DAHUA	4	DHI-HY-L121	Nos
5	Supply of wireless LoRa Sounder Strobe DHI-HY-L151 can be connected to the Addressable Fire Alarm Control Panel. Compatible with wireless gateway, Alarm Volume 75 dB-115 dB (A) at 3 m (9.84 ft) Alarm: Red indicator flashes once every second Fault: Yellow indicator flashes once every minute Standby: Green indicator flashes once every minute	DAHUA	4	DHI-HY-L151	Nos
6	Supply of Addressable Relay Module with Red Indicator LED Can be connected with Addressable panel (If required)	DAHUA	8	DHI-HY-1410B	Nos
7	Supply of 2 X 1.5 sq mm Aluminium Armed Cable (According to requirement) fire retardant cable	polycab/Havells/Finolex	200		RM
Option					
8	Supply of 2 X 1.5 sq mm copper Armed Cable (According to requirement) fire retardant cable	polycab/Havells/Finolex	200		RM